



designed for scientists



## IKA Pette vario 1-10 ml

/// Data Sheet

Lies comfortably in your hand with uncompromising precise performance: The IKA PETTE vario single-channel pipettes are used for many different applications in the modern laboratory. Color-coding simplifies rapid selection of the right pipette. The impact-resistant, UV-resistant and chemically resistant conical tip ensures reliable metering in the long-term.

Improved ergonomics as a result of replaceable handles

IKA pipettes include three interchangeable handles in various different shapes and materials in the delivery. The choice of the right handle for your particular hand means that the pipette can be adapted to suit your individual requirements.

[www.ika.com](http://www.ika.com)

Subject to technical changes



IKAworlwide



IKAworlwide /// #lookattheblue



@IKAworlwide



designed for scientists

This ergonomic optimization permits comfortable and wrist-friendly working, and ensures that the pipette sits in your hand perfectly in daily use for easy grasping of the working points. Precise and repeatable results are thus guaranteed.

#### Comfortable and rapid adjustment of the pipetting volume

The pipetting volume is adjusted in two stages (fine and coarse). Locking and unlocking of the volume is also carried out in the same way as fine adjustment by one hand using the multifunction button.

The set volume can be read off the display in large figures at any time, process-safe and clearly.

#### Straightforward ejection of the tip of the pipette

After the pipetting process, the tip of the pipette is ejected quickly and without time-consuming hand repositioning simply by pressing the central multifunction button. The round design means that the single-handed ejection works equally for both right-handed and left-handed users.

#### Robust and smooth

The piston and the tip cone of the pipette are made from PPSU (piston) and PPS (cone). Both of these materials are high-performance plastics which are characterized by high levels of chemical resistance and stiffness. The benefit of these high-quality materials for the user is primarily the consistent and low level of force required when absorbing and discharging the liquid to be pipetted.

#### Maintenance-friendly, process-secure and easy to clean

Regular cleaning and maintenance of the pipette guarantees a long service life for the product. The volume unit with piston and seal can be replaced completely in just a few hand movements. The equally simple assembly is acknowledged audibly by a click and is thus process-secure.

#### Adjusting safely and without the need for tools

If you detect deviations in the framework of calibration, the pipette will generally need to be adjusted. Tools are not needed for adjusting the IKA PETTE. The user thus saves valuable time in looking for the right tool. The pipette is subsequently secured against inadvertent adjustment.

#### Simplified acquisition, documentation and monitoring

Acquisition, documentation and monitoring of equipment and processes is of great importance in most laboratories. The serial number of the IKA PETTE can be scanned from a QR Code on the housing, easily and without transfer errors. The serial number and the pipette are thus uniquely linked.

#### Can be autoclaved at 121°C

The IKA PETTE is ideally suited to heat and high-pressure sterilization. Thanks to its simple construction, the pipette can be cleaned and autoclaved either in complete or in dismantled state.

#### Large range of pipette tips

All the PETTE fix and vario models are compatible with universal fit pipette tips from most manufacturers. Pipette tips having the standard color codes gray, yellow, and blue always fit on our pipettes, marked accordingly. This means that



designed for scientists

there is a wide range of pipette tips to choose from and you can rest assured that only suitable tips are fitted.





designed for scientists

## Technical Data

Design	Air displacement piston-operated pipette
Handling	mechanical
Volume	variable
Number of channels	1
Colour Code	Red
Nominal volume [ $\mu$ l]	10000
Volume min. [ $\mu$ l]	1000
Volume max. [ $\mu$ l]	10000
Increments [ $\mu$ l]	10
Accuracy with nominal volume [ $\mu$ l]	$\pm 60$
Accuracy with nominal volume [%]	$\pm 0.6$
Precision with nominal volume [ $\mu$ l]	$\pm 15$
Precision with nominal volume [%]	$\pm 0.15$
Accuracy with 50% of nominal volume [ $\mu$ l]	$\pm 40$
Accuracy with 50% of nominal volume [%]	$\pm 0.8$
Precision with 50% of nominal volume [ $\mu$ l]	$\pm 10$
Precision with 50% of nominal volume [%]	$\pm 0.2$
Accuracy with 10% of nominal volume [ $\mu$ l]	$\pm 30$
Accuracy with 10% of nominal volume [%]	$\pm 3$
Precision with 10% of nominal volume [ $\mu$ l]	$\pm 6$
Precision with 10% of nominal volume [%]	$\pm 0.6$
Certificate of conformity according to ISO 8655	yes
Autoclavable	yes
Piston material	PPSU
Dimensions (W x H x D) [mm]	30 x 222 x 63
Weight [kg]	0.108
Permissible ambient temperature [ $^{\circ}$ C]	5 - 40
Permissible relative humidity [%]	90