

Photos:



Accessories



English Software

The screenshot shows a software interface with the following sections:

- General Data:**
 - Sample: []
 - Rotor: []
 - Date: []
 - Unit: []
 - Temp: []
 - Speed: []
 - Time: []
 - Operator: []
- Parameter:**
 - Viscosity: [] mPa.s
 - Percentage: [] %
 - Buttons: START, STOP, Refresh
- Measurement Data Table:**

Serial number	Rotor	Speed	Temp	viscosity number	Percentage	Time
1						
2						
3						
4						
5						
6						
7						
8						
9						
10						
11						
12						
13						
14						
15						
16						
17						
18						
19						
20						

Specifications:

Model	RV-6T (NDJ-9ST)	RV-6M (NDJ-9S)
Test Range	1-6,000,000 mpa.s/cp	
Display	LCD	
Spindles	No. 1, 2, 3, 4 (Note: NO. 0 is optional, test range: 1-10 mpa.s)	
Rotating Speeds	0.1/ 0.3 / 0.6 / 1.5 / 3 / 6 / 12 / 30 / 60 rpm/min	
Interface	<input type="checkbox"/> RS232C Interface And Software <input type="checkbox"/> Temperature Sensor Interface	RS232C
Automatic Switch	free selection of proper rotating speed or Spindles number.	
Stable Cursor	Strip-type cursor fully charged displayed when reading basically stable	
Tolerance	<= 2%	
Repeat ability	± 1%	
Power	AC 100-240V/50-60HZ	
Working Condition	Temperature 5-35 degree Relative humidity no more than 80%	
Attachments	<input type="checkbox"/> No. 1, 2, 3, 4 Spindles <input type="checkbox"/> Adapter <input type="checkbox"/> Foundation Plate <input type="checkbox"/> Up-Down Frame <input type="checkbox"/> English Manual	
Outline (mm)	370×325×280 mm	
Packing (mm)	420×480×360 mm	
N.W./ G.W. (kg)	6.8 kg / 9kg	
H.S. Code	90278099	